

1ST SEM. 2018/19

PAGE 1 OF 3

UNIVERSITY OF ESWATINI

FINAL EXAMINATION PAPER

PROGRAMME

BACHELOR OF SCIENCE IN TEXTILE, APPAREL DESIGN AND MANAGEMENT, BACHELOR OF

CONSUMER SCIENCE AND CONSUMER

SCIENCE EDUCATION YEAR IV

COURSE CODE

: TAD407/TADM 411

TITLE OF PAPER

TAILORING

:

TIME ALLOWED

TWO (2) HOURS

INSTRUCTION

ANSWER QUESTION ONE (1) AND

ANY OTHER TWO (2) QUESTIONS

DO NOT OPEN THIS PAPER UNTIL PERMISSION HAS BEEN GRANTED BY THE CHIEF INVIGILATOR

PAGE 2 OF 3

TAD407 (M)

QUESTION 1 [COMPULSORY]

- a) Demonstrate your understanding of pressing by differentiating the following:
- i) Tailor's ham and seam roll
- ii) Professional ironing system and ironing steam press

(6 Marks)

b) Outline the guidelines for fitting tailored jackets?

(8 Marks)

- c) Using the relevant 1/4 scale measurements below, draft the following jacket basic blocks on the provided plain sheet:
- i) Jacket back with double slash (incorporate seam allowance at the CB)
- ii) Two piece sleeve

Measurements (cm):

Back width	: 37	Bicep	. 22
Bust	: 85	Sleeve length Armhole length	: 32 : 64 : 20
Shoulder to shoulder			
Waist	: 73		
Slash length	. 22	Sleeve hem +SA	: 5

lash length : 22

(20 Marks)

- d) Explain how you would adjust the test garment to address the following fit problems.
- i) Lapels gape or break (even though the bustline fits correctly)
- ii) The back vent is spread open

(6 Marks)

 $[TOTAL\ MARKS = 40]$

QUESTION 2

a) What is topstitching and fully explain how is it done on tailored coats.

(10 Marks)

b) Fully explain how a fully lined jacket differs from a partially lined jacket.

(4 Marks)

c) Identify and compare and contrast two (2) tailoring methods. Tabulate your answer.

(10 Marks)

d) List and describe three (3) ways that are used to finish seams in partially lined jackets.

(6 Marks)

 $[TOTAL\ MARKS = 30]$

PAGE 3 OF 3

TAD407 (M)

QUESTION 3

a) Hand stitches are used for a professional look in tailoring. State and briefly explain how to make **four (4)** hand stitches used in tailoring.

(10 Marks)

b) Fully explain how to cut, prepare and attach a backstay.

(4 Marks)

c) Clearly explain how to test the quality of sew-in interfacing in terms of resilience, flexibility and weight.

(6 Marks)

d) Why is it important to pre-shrink the garment fabric and lining before construction.

(2 Marks)

e) Give and describe two (2) ways you can employ to pre-shrink fusible interfacing.

(8 Marks)

[TOTAL MARKS = 30]

QUESTION 4

a) Fabric preparation before construction is critical. State two (2) consequences of cutting fabric off grain.

(2 Marks)

b) Give seven (7) tips that guided you when pressing the tailored jacket.

(14 Marks)

c) Explain how you ensured that the jacket had minimal fabric thickness and a crisp custom finish.

(5 Marks)

- d) Describe the following terms by clearly drawing a distinction between them.
- i) Perfectly pressed
- ii) Over pressed
- iii) Under pressed

(9 Marks)

[TOTAL MARKS = 30]